

AC OEM — SPLIT PHASE

ACData

AC Power Surge Protection

| Model | Operating Voltage | Surge Current Capacity | Fault Current Rating | Nominal Current (In) | SPD Type | M COV | Protection Rating (VPR) | Enclosure Type |
|---------------|--------------------|------------------------|------------------------------|----------------------|----------|-------|-------------------------|-----------------------|
| AC2040-01-NA | 1Φ 120/240 3W+G | 40kA L-N | 10kA with No Breaker | 10kA | Type 1 | 140V | 600V | PVC Plastic Type 1 |
| | | 40kA L-G | | | | 140V | 1000V | |
| | | 40kA N-G | | | | 140V | 600V | |
| | | 40kA L-L | | | | 280V | 1000V | |
| AC2040-01W-NA | 1Φ 120/240 3W+G | 40kA L-N | 10kA with No Breaker | 10kA | Type 1 | 140V | 600V | PVC Plastic Type 4 |
| | | 40kA L-G | | | | 140V | 1000V | |
| | | 40kA N-G | | | | 140V | 600V | |
| | | 40kA L-L | | | | 280V | 1000V | |
| AC2040-02-NA | 1Φ 120/240 3W+G | 40kA L-N | 65kA with 200 Amp Breaker | 10kA | Type 2 | 140V | 800V | PVC Plastic Type 1 |
| | | 40kA L-G | | | | 140V | 1200V | |
| | | 40kA N-G | | | | 140V | 600V | |
| | | 40kA L-L | | | | 280V | 1200V | |
| AC2040-02W-NA | 1Φ 120/240 3W+G | 40kA L-N | 65kA with 200 Amp Breaker | 10kA | Type 2 | 140V | 800V | PVC Plastic Type 4 |
| | | 40kA L-G | | | | 140V | 1200V | |
| | | 40kA N-G | | | | 140V | 600V | |
| | | 40kA L-L | | | | 280V | 1200V | |
| AC2060-01-NA | 1Φ 120/240 3W+G | 60kA L-N | 10kA with No Breaker | 20kA | Type 1 | 140V | 600V | PVC Plastic Type 1 |
| | | 60kA L-G | | | | 140V | 1000V | |
| | | 60kA N-G | | | | 140V | 600V | |
| | | 60kA L-L | | | | 280V | 1000V | |
| AC2060-01W-NA | 1Φ 120/240 3W+G | 60kA L-N | 10kA with No Breaker | 20kA | Type 1 | 140V | 600V | PVC Plastic Type 4 |
| | | 60kA L-G | | | | 140V | 1000V | |
| | | 60kA N-G | | | | 140V | 600V | |
| | | 60kA L-L | | | | 280V | 1000V | |
| AC2060-02-NA | 1Φ 120/240 3W+G | 60kA L-N | 65kA with 200 Amp Breaker | 20kA | Type 2 | 140V | 800V | PVC Plastic Type 1 |
| | | 60kA L-G | | | | 140V | 1200V | |
| | | 60kA N-G | | | | 140V | 600V | |
| | | 60kA L-L | | | | 280V | 1200V | |
| AC2060-02W-NA | 1Φ 120/240 3W+G | 60kA L-N | 65kA with 200 Amp Breaker | 20kA | Type 2 | 140V | 800V | PVC Plastic Type 4 |
| | | 60kA L-G | | | | 140V | 1200V | |
| | | 60kA N-G | | | | 140V | 600V | |
| | | 60kA L-L | | | | 280V | 1200V | |
| AC2080-01-NA | 1Φ 120/240 3W+G | 80kA L-N | 10kA with No Breaker | 20kA | Type 1 | 140V | 600V | PVC Plastic Type 1 |
| | | 80kA L-G | | | | 140V | 1000V | |
| | | 80kA N-G | | | | 140V | 600V | |
| | | 80kA L-L | | | | 280V | 1000V | |
| AC2080-01W-NA | 1Φ 120/240 3W+G | 80kA L-N | 10kA with No Breaker | 20kA | Type 1 | 140V | 600V | PVC Plastic Type 4 |
| | | 80kA L-G | | | | 140V | 1000V | |
| | | 80kA N-G | | | | 140V | 600V | |
| | | 80kA L-L | | | | 280V | 1000V | |
| AC2080-02-NA | 1Φ 120/240 3W+G | 80kA L-N | 65kA with 200 Amp Breaker | 20kA | Type 2 | 140V | 800V | PVC Plastic Type 1 |
| | | 80kA L-G | | | | 140V | 1200V | |
| | | 80kA N-G | | | | 140V | 600V | |
| | | 80kA L-L | | | | 280V | 1200V | |
| AC2080-02W-NA | 1Φ 120/240 3W+G | 80kA L-N | 65kA with 200 Amp Breaker | 20kA | Type 2 | 140V | 800V | PVC Plastic Type 4 |
| | | 80kA L-G | | | | 140V | 1200V | |
| | | 80kA N-G | | | | 140V | 600V | |
| | | 80kA L-L | | | | 280V | 1200V | |

- Operating Temperatures - -40° C to +80° C
- Suppression Connection - Hardwire (w/four 12 AWG wires)
- Form C Contact Connection: No Form C Contact



GS-07F-0435V



Certified to
ISO 9001:2000



Raycap

REV 010410

Raycap, Inc. 806 W. Clearwater Loop • Post Falls • Idaho • 83854 • USA
Phone 208.777.1166 • Toll Free 800.890.2569 • Fax 208.777.4466 • www.raycapsurgeprotection.com